



## DS-2CD2012-I 1.3MP IR Mini Bullet Camera



### Key features

- 1.3 megapixel high resolution
- HD video output
- Low illumination
- IP66 rating
- IR range: up to 30m
- True day / night

### Dimensions



### Specifications

| DS-2CD2012-I                |                                                                                                                      |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Camera</b>               |                                                                                                                      |
| Image sensor                | 1/3" progressive scan CMOS                                                                                           |
| Min. illumination           | 0.01 lux @F1.2, AGC ON<br>0 lux with IR                                                                              |
| Shutter time                | 1/25s ~ 1/100,000s                                                                                                   |
| Lens                        | 6mm @F1.2 (4mm, 12mm optional)                                                                                       |
| Lens mount                  | M12                                                                                                                  |
| Day & night                 | IR cut filter with auto switch                                                                                       |
| Digital noise reduction     | 3D DNR                                                                                                               |
| <b>Compression Standard</b> |                                                                                                                      |
| Video compression           | H.264 / MPEG4 / MJPEG                                                                                                |
| Bit rate                    | 32 Kbps ~ 16 Mbps                                                                                                    |
| <b>Image</b>                |                                                                                                                      |
| Max. Image Resolution       | 1280 × 960                                                                                                           |
| Frame rate                  | 50Hz: 25fps (1280 × 960), 25fps (1280 × 720)<br>60Hz: 30fps (1280 × 960), 30fps (1280 × 720)                         |
| Image settings              | Saturation, brightness, contrast, sharpness adjustable through client software or web browser                        |
| <b>Network</b>              |                                                                                                                      |
| Network storage             | NAS (iSCSI optional)                                                                                                 |
| Alarm trigger               | motion detection, tampering alarm, network disconnect, IP address conflict, storage exception                        |
| Protocols                   | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional) |
| Interoperability            | ONVIF, PSIA, CGI                                                                                                     |
| Security                    | User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark                            |
| <b>Interface</b>            |                                                                                                                      |
| Communication interface     | 1 RJ45 10 M / 100 M Ethernet interface                                                                               |
| <b>General</b>              |                                                                                                                      |
| Operating conditions        | -10 °C ~ 60 °C (14°F ~ 140 °F) humidity 90% or less (non-condensing)                                                 |
| Power supply                | 12 VDC ± 10% , PoE (802.3af)                                                                                         |
| Power consumption           | max. 4W (ICR on: max. 5.5W)                                                                                          |
| Weather proof rating        | IP66                                                                                                                 |
| IR range                    | Up to 30m                                                                                                            |
| Dimension                   | 60.4 x 76.5 x 138.1mm                                                                                                |
| Weight                      | 300g                                                                                                                 |

### Available model

DS-2CD2012-I

\* Product picture and technical specs subject to change without previous notice.  
For further information, please contact our local sales team.